

## CLAIMS

1. Method for manufacture of toroidal transformers,  
5 the method comprising the steps of:

arranging a coil around the periphery of at least  
one hollow bobbin of elongated shape and of flexible  
material;

bending said at least one bobbin, together with said  
10 coil, so that the bobbin ends are brought towards each  
other, one of said bobbin ends defining an opening; and  
feeding a ribbon of magnetic material through said  
opening, so that said ribbon is being wound a required  
amount of tightly packed winding turns inside said bobbin  
15 until essentially the whole interior cavity of said  
bobbin is filled, said ribbon thereby forming a core.

2. Method according to claim 1, comprising the  
additional step of:

20 cutting said ribbon at a desired length after having  
fed said ribbon through said opening.

3. Method according to any one of claims 1 or 2,  
comprising the additional step of:

25 pre-bending said ribbon at the end intended to first  
be fed through said opening.

4. Method according to any one of claims 1 to 3,  
comprising the additional step of:

30 providing a part of said ribbon first being fed into  
the bobbin essentially corresponding to the first wound  
winding inside said bobbin of said ribbon, on the side  
facing the inner curvature of the interior hollow cavity

25

of the bobbin, with a layer having a low coefficient of friction for facilitating sliding of said ribbon while being wound inside said bobbin.

5           5. Method according to claim 4, wherein said layer is provided by at least one of an adhesive tape having a first side with low coefficient of friction and a second side being adhesive, a coating with low coefficient of friction, and a fluid.

10

6. Method according to any one of claims 1 to 5, comprising the additional step of:

          arranging a flexible transmission element so that it is in continuous co-operation with the innermost winding  
15 of said ribbon, further facilitating sliding of said ribbon while being wound inside said bobbin, thus forming the core.

7. Method according to any one of claims 5 or 6,  
20 comprising the additional step of:

          arranging mediating means in connection to said ribbon for mediating co-operation between said flexible transmission element and said ribbon, said mediating means engaging with said flexible transmission element  
25 over a distance corresponding to at least a fraction of the innermost winding inside said bobbin of said ribbon.

8. Method according to claim 7, wherein said mediating means comprises a from said ribbon protruding  
30 part of said layer.

26

9. Method according to any one of claims 1 to 8,  
wherein the step of feeding said ribbon of magnetic  
material through said opening further comprises:

rotating said bent bobbin together with said coil;  
5 and

stopping, essentially instantaneously, the rotation  
of said bent bobbin together with said coil.

10. Method according to any one of claims 1 to 9,  
10 wherein the step of feeding said ribbon of magnetic  
material through said opening further comprises:

injecting a medium through said opening, thereby  
creating a variable gap between the outer curvature of  
the interior of said hollow bobbin, being in a bent  
15 position, and said ribbon; and

leading said medium out from said hollow bobbin.

11. Method according to any one of claims 1 to 10,  
wherein said method is performed in a magnetic field.

20

12. Bobbin for manufacture of toroidal transformers,  
essentially comprising an elongated tube, characterised  
by:

said elongated tube being made by a flexible mate-  
25 rial and adapted to be bent, so that the ends of said  
elongated tube may be brought towards each other, one of  
said ends of said elongated tube defining an opening; and  
said elongated tube having an essentially rectang-  
ular interior hollow cross-section.

30

13. System for manufacture of toroidal transformers,  
the system comprising:

27

means for performing said method for manufacture of toroidal transformers, according to any one of claims 1 to 11.

5           14. Toroidal transformer manufactured by said method for manufacture of toroidal transformers, according to any one of claims 1 to 11.

10           15. Use of a toroidal transformer according to claim 14 in electrical equipment, such as adaptors.